

PRODUCT FICHE		
Energy Label Directive		
Model		ADT 606-2 B
Annual Energy Consumption( AEC hood)(kWh/a)		58,3
Energy Efficiency Class		A
Fluid Dynamic Efficiency (FDE hood)		29,1
Fluid Dynamic Efficiency Class		A
Lighting Efficiency (LE hood) (lux/watt)		34
Lighting Efficiency Class		A
Grease Filtering Efficiency		86,0
Grease Filtering Efficiency Class		B
Air flow (m³/h) (min. and max. setting)		204-425
Air flow (m³/h) (boost setting)		710
Sound power level (dB) (min. and max. setting)		43-60
Sound power level (dB) (boost setting)		71
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-

7703330202      185373333 AA

INSTRUCTION BOOKLET		
Information for domestic range hoods		
Comply with EU directive 2009/125/EC Regulation No 66/2014		
Brand	ARÇELİK	
Model	ADT 606-2 B	
Annual Energy Consumption( AEC hood)(kWh/a)		58,3
Time increase factor (f)		0,9
Fluid Dynamic Efficiency (FDE hood)		29,1
Energy Efficiency Index (EEI hood)		54,6
Measured air flow rate at best efficiency point (QBEP ) (m³/h)		378
Measured air pressure at best efficiency point (PBEP) (Pa)		456
Maximum air flow (Q max) (m³/h)		710
Measured electric power input at best efficiency point(WBEP) (W)		160
Nominal power of the lighting system (WL)(W)		5,5
Average illumination of the lighting system on the cooking surface (E middle)(lux)		189
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-
Sound power level (LWA)(dB)		60