

PRODUCT FICHE		
Energy Label Directive		
Model		ADE 605-3 G
Annual Energy Consumption(AEC hood)(kWh/a)		68,3
Energy Efficiency Class		B
Fluid Dynamic Efficiency (FDE hood)		23,8
Fluid Dynamic Efficiency Class		B
Lighting Efficiency (LE hood) (lux/watt)		32,7
Lighting Efficiency Class		A
Grease Filtering Efficiency		65,5
Grease Filtering Efficiency Class		D
Air flow (m³/h) (min. and max. setting)		240-600
Air flow (m³/h) (boost setting)		-
Sound power level (dB) (min. and max. setting)		50-69
Sound power level (dB) (boost setting)		-
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-

7704330115 185373904 AA

INSTRUCTION BOOKLET		
Information for domestic range hoods		
Comply with EU directive		
Model	ADE 605-3 G	
Annual Energy Consumption(AEC hood)(kWh/a)		68,3
Time increase factor (f)		1,1
Fluid Dynamic Efficiency (FDE hood)		23,8
Energy Efficiency Index (EEI hood)		64,2
Measured air flow rate at best efficiency point (QBEP) (m³/h)		366
Measured air pressure at best efficiency point (PBEP) (Pa)		375
Maximum air flow (Q max) (m³/h)		600
Measured electric power input at best efficiency point(WBEP) (W)		160
Nominal power of the lighting system (WL)(W)		5.5
Average illumination of the lighting system on the cooking surface (E middle)(lux)		180
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-
Sound power level (LWA)(dB)		69