

PRODUCT FICHE		
Energy Label Directive		
Model	BDE 6040 B	
Annual Energy Consumption(AEC hood)(kWh/a)	59	
Energy Efficiency Class	C	
Fluid Dynamic Efficiency (FDE hood)	20,3	
Fluid Dynamic Efficiency Class	C	
Lighting Efficiency (LE hood) (lux/watt)	32	
Lighting Efficiency Class	A	
Grease Filtering Efficiency	66,0	
Grease Filtering Efficiency Class	D	
Air flow (m³/h) (min. and max. setting)	226-408	
Air flow (m³/h) (boost setting)	-	
Sound power level (dB) (min. and max. setting)	43-56	
Sound power level (dB) (boost setting)	-	
Measured power consumption in standby mode (Ps) (W)	0,25	
Measured power consumption off mode (Po)(W)	-	

7704331210 185373383 AA

INSTRUCTION BOOKLET		
Information for domestic range hoods		
Comply with EU directive 2009/125/EC Regulation No 66/2014		
Brand	Beko	
Model	BDE 6040 B	
Annual Energy Consumption(AEC hood)(kWh/a)		59
Time increase factor (f)		1,3
Fluid Dynamic Efficiency (FDE hood)		20,3
Energy Efficiency Index (EEI hood)		70,6
Measured air flow rate at best efficiency point (QBEP) (m³/h)		271,1
Measured air pressure at best efficiency point (PBEP) (Pa)		319
Maximum air flow (Q max) (m³/h)		408
Measured electric power input at best efficiency point(WBEP) (W)		118
Nominal power of the lighting system (WL)(W)		5.5
Average illumination of the lighting system on the cooking surface (E middle)(lux)		175
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-
Sound power level (LWA)(dB)		56