

PRODUCT FICHE		
Energy Label Directive		
Model	ADE 605 HB	
Annual Energy Consumption(AEC hood)(kWh/a)		56
Energy Efficiency Class		B
Fluid Dynamic Efficiency (FDE hood)		21,0
Fluid Dynamic Efficiency Class		C
Lighting Efficiency (LE hood) (lux/watt)		30,0
Lighting Efficiency Class		A
Grease Filtering Efficiency		60,0
Grease Filtering Efficiency Class		E
Air flow (m³/h) (min. and max. setting)		220-400
Air flow (m³/h) (boost setting)		-
Sound power level (dB) (min. and max. setting)		46-59
Sound power level (dB) (boost setting)		-
Measured power consumption in standby mode (Ps) (W)		-
Measured power consumption off mode (Po)(W)		-

7704331223 185373655 AB

INSTRUCTION BOOKLET		
Information for domestic range hoods		
Comply with EU directive 2009/125/EC Regulation No 66/2014		
Brand	ARÇELİK	
Model	ADE 605 HB	
Annual Energy Consumption(AEC hood)(kWh/a)		56
Time increase factor (f)		1,3
Fluid Dynamic Efficiency (FDE hood)		21,0
Energy Efficiency Index (EEI hood)		68,0
Measured air flow rate at best efficiency point (QBEP) (m³/h)		240,0
Measured air pressure at best efficiency point (PBEP) (Pa)		350,0
Maximum air flow (Q max) (m³/h)		400
Measured electric power input at best efficiency point(WBEP) (W)		115,0
Nominal power of the lighting system (WL)(W)		7.0
Average illumination of the lighting system on the cooking surface (E middle)(lux)		175.0
Measured power consumption in standby mode (Ps) (W)		-
Measured power consumption off mode (Po)(W)		-
Sound power level (LWA)(dB)		59