

| PRODUCT FICHE                                       |             |         |
|---|-------------|---------|
| Energy Label Directive                              |             |         |
| Model   | ADE 906-2 G |         |
| Annual Energy Consumption( AEC hood)(kWh/a)         |             | 60,2    |
| Energy Efficiency Class                             |             | A       |
| Fluid Dynamic Efficiency (FDE hood)                 |             | 30,4    |
| Fluid Dynamic Efficiency Class                      |             | A       |
| Lighting Efficiency (LE hood) (lux/watt)            |             | 31      |
| Lighting Efficiency Class                           |             | A       |
| Grease Filtering Efficiency                         |             | 75,3    |
| Grease Filtering Efficiency Class                   |             | C       |
| Air flow (m³/h) (min. and max. setting)             |             | 220-441 |
| Air flow (m³/h) (boost setting)                     |             | 712     |
| Sound power level (dB) (min. and max. setting)      |             | 43-58   |
| Sound power level (dB) (boost setting)              |             | 69      |
| Measured power consumption in standby mode (Ps) (W) |             | 0,25    |
| Measured power consumption off mode (Po)(W)         |             | -       |

| INSTRUCTION BOOKLET  |             |       |
|--|-------------|-------|
| Information for domestic range hoods   |             |       |
| Comply with EU directive 2009/125/EC Regulation No 66/2014                         |             |       |
| Brand  | ARÇELİK     |       |
| Model  | ADE 906-2 G |       |
| Annual Energy Consumption( AEC hood)(kWh/a)  |             | 60,2  |
| Time increase factor (f)   |             | 0,9   |
| Fluid Dynamic Efficiency (FDE hood)  |             | 30,4  |
| Energy Efficiency Index (EEI hood)   |             | 54,1  |
| Measured air flow rate at best efficiency point (QBEP ) (m³/h)                     |             | 424,1 |
| Measured air pressure at best efficiency point (PBEP) (Pa)                         |             | 434,6 |
| Maximum air flow (Q max) (m³/h)  |             | 712   |
| Measured electric power input at best efficiency point(WBEP) (W)                   |             | 168,6 |
| Nominal power of the lighting system (WL)(W)                                       |             | 5,0   |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) |             | 155   |
| Measured power consumption in standby mode (Ps) (W)                                |             | 0,25  |
| Measured power consumption off mode (Po)(W)  |             | -     |
| Sound power level (LWA)(dB)  |             | 58    |