

SPX-810

Professional PA Speaker System

introduces a 700 Watts Professional 2-Way PA Speaker System with Exceptional LF Response, Tremendous Efficiency and Unmatched Intelligible Sound.

- Two 15" High Performance LF Transducers and a High Frequency Titanium Compression Horn Driver housed in an acoustically treated Bass Reflex Trapezoidal enclosure with ultra-modern paint finish.
- Sturdy and Aesthetically Designed Metal Grill lends both protection to the speakers as well as superb looks to the cabinet.
- Well designed heavy duty metal handles ensure hassle-free mobility and transportation.
- Suitable for both indoor and outdoor sound reinforcement applications Ideal for Auditoria... DJs... Live Concerts... Discos... etc
- logo engraved on the both side of the cabinet lends uniqueness & freshness to the design and makes it difficult to imitate.

Specifications

INPUT POWER	700W RMS
CONFIGURATION	Two Way
FREQUENCY RESPONSE	40-20,000Hz
COMPONENTS	2 × 15" LF Speaker
	16" × 7" Dynamic HF Unit
SPL (1W/1m)	103dB
MAX. RATED SPL	131dB
NOMINAL IMPEDANCE	4Ω
CROSSOVER FREQUENCY	2kHz
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W530 × H1210 × D510mm
WEIGHT	65.00kg



700
WATTS

2
WAY