SRX-510

Professional PA Speaker System

introduces a 400 Watts Professional 2-Way PA Speaker System with Exceptional Efficiency, long through and Unmatched Intelligible Sound.

- Two 15" High Performance LF Transducers and a High Frequency Compression Horn Driver housed in an acoustically treated Bass Reflex enclosure with ultra-modern paint finish.
- Sturdy and Aesthetically Designed Metal Grill lends both protection to the speakers as well as superb looks to the cabinet.
- Well designed heavy duty metal handles ensure hassle-free mobility and transportation.
- Suitable for both indoor and outdoor sound reinforcement applications Ideal for Auditoria...
 DJs··· Live performances··· etc
- logo engraved on both sides of the cabinet lends uniqueness & freshness to the design and makes it difficult to imitate.

Specifications

INPUT POWER	400W RMS
CONFIGURATION	Two Way
FREQUENCY RESPONSE	50-20,000Hz
COMPONENTS	2 × 15" LF Speaker
	4" × 10" Dynamic HF Unit
SPL (1W/1m)	101dB
MAX. RATED SPL	127dB
NOMINAL IMPEDANCE	8 Ω
CROSSOVER FREQUENCY	6kHz
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W530 × H1210 × D510mm
WEIGHT	65.00kg
	The state of the s

