

SWX-1000

PA Subwoofer System



The SWX-1000 is a high reliability super power SUBWOOFER system with exceptional distortion-free low frequency response. It is fitted with a 18" LF driver having 5" inside/outside voice coil wound on a polyimide fibre glass former. The speaker has an aluminium demodulating ring for better heat dissipation and a specially treated cone for water splash resistance. The cabinet is rugged and specially braced to withstand intense vibrations. Wide port design for increased efficiency. A stand adapter has been provided at the top of the cabinet for pole mounting a full range speaker system. The cabinet is fitted with heavy duty handles for ease of transportation. The strong metal grille protects the speaker from unavoidable strokes.

This subwoofer system combines aesthetic design, modern appearance high reliability and excellent performance.



Specifications

INPUT POWER	1000W RMS
CONFIGURATION	One Way
FREQUENCY RESPONSE	36-200Hz
LOW FREQUENCY SPEAKER	1 x 18" Ø5" Inside/Outside Wound Voice Coil
SPL at (1W/1m)	99dB
MAX. RATED SPL	129dB
NOMINAL IMPEDANCE	8Ω
PORT	Free Flow Flared
INPUT CONNECTORS	Terminal Strip + Speakon
DIMENSIONS	W610 × H845 × D540 mm
WEIGHT	53.00kg