

SWX-2600

PA SUBWOOFER SYSTEM



Rugged and high power professional passive subwoofer system driven by two efficient 18"LF drivers. Housed in an optimally designed bass reflex enclosure to provide superior bass response with higher power handling capacity. Strong and durable wooden enclosure is well braced internally and attractively paint finished externally. Protective grille has robust design to provide required protection to the speaker and professional appearance to the product. The enclosure is fitted with four heavy duty handles, a recessed terminal plate and six indexed feet for ease of stacking. Two speakon connectors for quick and convenient connections. Suitable for all types of installed and touring applications.

Specifications

POWER RATING	2600W RMS/5200W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	35-200Hz
LOW FREQUENCY SPEAKER	2 x 18" with Ø5" Inside/Outside Wound Voice Coil
SPL at (1W/1m)	100dB
MAX. RATED SPL	134dB
NOMINAL IMPEDANCE	4Ω
PORT	Free Flow Flared
INPUT CONNECTORS	2 × Speakon
DIMENSIONS	W1100 × H625 × D790 mm
WEIGHT	105.00kg approx.

Design and Specifications are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances. We cannot be held responsible for printing errors, should they occur. is a registered trademark of Ahuja Radios in India and other countries. © Copyright Ahuja Radios, 2019. All rights reserved. Any unauthorized reproduction or use of logos, images or design elements is strictly prohibited by law. No part of this compilation may be reproduced in any manner or translated without written permission.