

SWX-810

PA SUBWOOFER SYSTEM



Rugged and high power professional passive subwoofer system driven by One efficient 18" LF driver. Housed in an specially designed bass reflex enclosure to provide superior bass response with higher power handling capacity. Strong and durable wooden enclosure is well braced internally and attractively paint finished externally. Protective grille has robust design to provide required protection to the speaker and professional appearance to the product. The enclosure is fitted with four heavy duty handles, a recessed terminal plate and four indexed feet for ease of stacking. Speakon connector and Terminal Strip are provided for quick and convenient connections. Suitable for all types of installed and touring applications.

Specifications

POWER RATING	800W RMS/1600W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	38-200Hz
LOW FREQUENCY SPEAKER	1 x 18" with Ø4" Inside/Outside Wound Voice Coil
SPL at (1W/1m)	98dB
MAX. RATED SPL	127dB
NOMINAL IMPEDANCE	8Ω
PORT	Free Flow Flared
INPUT CONNECTORS	Speakon + Terminal Strip
DIMENSIONS	W538 × H710 × D700 mm
WEIGHT	55.00kg approx.

Design and Specifications are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances. We cannot be held responsible for printing errors, should they occur. is a registered trademark of Ahuja Radios in India and other countries. © Copyright Ahuja Radios, 2019. All rights reserved. Any unauthorized reproduction or use of logos, images or design elements is strictly prohibited by law. No part of this compilation may be reproduced in any manner or translated without written permission.