

Compact & portable 200W, 2-Way PA speaker system comprises of a high performance 10" LF speaker and a reliable HF driver. Ideal for use in a wide variety of speech & music applications.

- Rugged & portable bass reflex cabinet moulded with a special polypropylene plastic material.
- Built with a 10" 200W reliable & efficient LF speaker.
- High performance HF driver made with a 1.0" voice coil & titanium diaphragm.
- Equipped with a professional passive crossover network using low resistance inductors & high quality metallised polyester capacitors.
- Special cabinet profile allows functional flexibility in various professional audio applications such as stage monitors, live sound reinforcement and installed sound systems.
- A pole socket is provided at the bottom for easy stand mounting as well as wall mounting.
- Three integrated M8 flying points on top side and right side of the cabinet enable vertical and horizontal suspension applications.

## **SPECIFICATIONS**

Power Rating	200W RMS	MAX. Rated SPL	117dB
Configuration	Two Way	Nominal Impedance	8Ω
Frequency Response	65-18,000Hz	Port	Free Flow Flared
Low Frequency Speaker	1 x 10", Ø 2.0" CCAW Voice Coil	Input Connectors	1/4" Phone Jack + Push Terminals
High Frequency Unit	Dynamic Horn, Ø1.0" Voice Coil	Dimensions	W325 × H485 × D255 mm
SPL at (1W/1m)	94dB	Weight	9.70kg approx.