

introduces a compact & exquisite 300W, 2-Way PA speaker system model VX-300. It comprises of a high performance 12" LF speaker and a reliable HF driver. Ideal for use in a wide variety of speech & music applications.

- Rugged & portable bass reflex cabinet moulded with a special polypropylene plastic material.
- Built with a 12" 300W reliable & efficient LF speaker.
- High performance HF driver made with a 1.75" voice coil & titanium diaphragm.
- Equipped with a professional two way passive crossover network using low resistance inductors & high quality metallised polyester capacitors.
- Special cabinet profile allows functional flexibility in various professional audio applications such as stage monitors, live sound reinforcement and installed sound systems.
- A pole socket is provided at the bottom for easy stand mounting as well as wall mounting.
- Three integrated M8 flying points on top side and right side of the cabinet enable vertical and horizontal suspension applications.

## **SPECIFICATIONS**

Power Rating	300W RMS	MAX. Rated SPL	122dB
Configuration	Two Way	Nominal Impedance	8Ω
Frequency Response	60-18,000Hz	Port	Free Flow Flared
Low Frequency Speaker	1 x 12", Ø 2.5" CCAW Voice Coil	Input Connectors	Speakon + Push Terminals
High Frequency Unit	Dynamic Horn, Ø1.75" Voice Coil	Dimensions	W385 × H585 × D305 mm
SPL at (1W/1m)	97dB	Weight	15.80kg approx.